

BELT/DISC FINISHING MACHINE

- Sanding outside curves
 - Sanding irregular shaped objects
1. Wear safety glasses at all times when operating the belt/disc sander.
 2. Wear a dust mask or respirator when using the belt/disc sander for prolonged periods of time.
 3. Keep the sanding disc well glued to the disc plate at all times.
 4. If the sanding disc rotates in a counterclockwise direction, position the material to be sanded from the center of the disc to the left edge. If positioned in this manner the sanding action will help to hold the stock down on the table. If the stock is positioned from the center of the disc to the right edge of the disc the sanding action will pick the edge of the stock up and created an unsafe condition.
 5. Do not reach across the sanding disc to turn the sander on or off. Your arm or hand may touch the edge of the rotating disc and cause a serious cut or entanglement. Move to the front of the sander and turn the machine off.
 6. Never wear loose, or baggy clothes when operating the belt/disc sander.
 7. Disconnect the electrical power to the sander when changing the belt or disc or making major adjustments.
 8. Try to position yourself so that sanding dust will not be thrown toward the breathing zone.
 9. Hold stock steady as it is being sanded, but do not put so much pressure on the sanding disc or belt that the sander slows down.
 10. Do not allow hands or fingers to touch the belt or disc when sanding.